

SPECIFICATIONS

ENGINE	
Make/Model	Yanmar/4TNV 106T
Rated output	72.0kW / 2200 min ⁻¹
Maximum torque	361.6~394.0Nm/1400 min ⁻¹
Cylinders/displacement	4/4412 ml
Engine lubrication	14.0 litres
Cooling system	15.0 litres
Fuel tank capacity	108 litres
Fuel consumption (65% of full load)	14.1 litres/hour
Electrical system	12V/60A
HYDRAULIC SYSTEM	
Hydraulic reservoir capacity	64 litres
Auxiliary hydraulic flow	88 litres/minute
System operating pressure	20.6 MPa
DIMENSIONS & WEIGHT	
Operating weight	4850 kg
Overall width without bucket	1860 mm
Overall height	2320 mm
Overall length with bucket	3985 mm
Front clearance radius with bucket	2435 mm
Rear clearance radius	1755 mm
Angle of departure	29°
Maximum lift height to bucket pin	3205 mm
Dump height fully raised	2430 mm
Max. dump angle fully raised	38.7°
Max. bucket rollback at ground level	31.4°
Reach fully raised	985 mm
BUCKET	
Width	1960 mm
Capacity SAE heaped	0.579 m ³
PERFORMANCE	
Tipping load SAE 732	3200 kg
Operating Capacity SAE J818	1120 kg
Breakout force bucket cylinders	38.5 kN
Breakout force lift arm cylinders	38.0 kN
CYCLE TIME	
Raise - full load	4.8 sec
Lower - no load	3.1 sec
Dump - full load	3.3 sec
Curl - full load	2.4 sec

SHERRIN
Rentals

BRISBANE • DARWIN • TOOWOOMBA • SUNSHINE COAST

132 138

Email - info@sherrinrentals.com.au Web - www.sherrinrentals.com.au



TL15 Track Loader